

Model: JLV-12036A / JLV-24036A Constant voltage 12V/24V
Constant voltage AC/DC ADAPTER: 12V 3A 36W / 24V 1.5A 36W



Size: 120*50*30mm

| Specification | JLV-12036A | JLV-24036A |
|--------------------------|---------------------------------------|-------------------|
| Input Voltage | 100~250V AC | |
| Input Frequency Range | 47~63Hz | |
| Input Ampere | 0.33A@220VAC Max. | 0.32A@220VAC Max. |
| Input Inrush Current | 30A@220VAC Max. | |
| Input Leakage Current | 5mA@220VAC Max. | |
| Output Voltage | 12V | 24V |
| Output Current | 3A | 1.5A |
| Output Power | 36W | |
| Setup Time | 1500ms@220VAC | |
| Efficiency (Typ.) | >83% | |
| Ripple & Noise (max.) | <500mV | |
| Line regulation | <2% | |
| Load regulation | <1% | |
| Withstand Voltage | I/P-O/P: 3.75KVAC I/P-GND: 1.5KVAC | |
| Isolation Resistance | I/P-O/P: 100M ohms /500VDC/25°C 70%RH | |
| Working Environment | -20~50 °C | 20%~92% RH |
| Storage Environment | -40~80 °C | 10%~95% RH |
| IP Rate | IP50 | |
| Short circuit protection | YES, Hiccup mode | |
| Overload protection | YES, Voltage drop mode | |
| Net Weight | 205g | |
| Dimension(mm) | 120*50*30mm | |
| Plug Available | Refer the right chart | |

Features:

1. Compact size
2. High efficiency professional IC for LED
3. Wide input range (100~250VAC)
4. Stable constant voltage output
5. Fully Seally IP50
6. 100% burn-in tested
7. Super cooling design, long life span
8. Overload/short circuit protection
9. Proven reliable quality

Plugs Available:

| | Type | Plug Shape adapter | Outlet Type |
|---------|------|--------------------|-------------|
| TypeC | | | |
| TypeB | | | |
| Type B3 | | | |
| Type SE | | | |
| Type BF | | | |
| Type A | | | |
| Type 0 | | | |

* Individual box packing